

# Outdoor Microphone Accessories and Cables

## **AC0001**

### ***Calibration Control Box for Types 41AM/41CN***

The AC0001 is a control box with local and remote facilities for switching on/off the Actuator Calibration of the Outdoor Microphone Systems Types 41AM and 41CN. It also has a BNC output for analysing the signals from these Outdoor Microphone Systems. It can be connected to a 12 – 18V DC mains/line adapter for powering the Types 41AM and 41CN.

## **AL0001**

### ***Desiccator for Type 41AL***

The AL0001 is a desiccator unit which is mounted on the bottom of the Environmental Microphone Type 41AL and extends the time in which the Type 41AL can be used outdoors.

## **AM0009**

### ***Windscreens for Types 41AM/41CN/41AL***

The AM0009 is a set of five open-cell-structure foam windscreens for mounting on the Outdoor Microphone Systems Types 41AM and 41CN, and the Environmental Microphone Type 41AL.

## **AM0052**

### ***Complete Windscreen for Types 41AM/41CN/41AL***

The AM0052 is a windscreen, complete with anti-bird spikes, for mounting on the Outdoor Microphone Systems Types 41AM and 41CN, and the Environmental Microphone Type 41AL.

## **AM0089**

### ***Low-noise Windscreen***

Spherical windscreen for Types 41AM/CN. Fits directly over the existing windscreen, accommodating the anti-bird spikes. Open-cell foam structure 20ppi, 150 mm diameter.

## **RA0009**

### ***Adapter for Pistonphone calibration***

The RA0009 is an adapter for calibrating the Outdoor Microphone System Type 41AM. It fits over the rain protection cap of the Type 41AM and permits *in-situ* calibration using a Pistonphone such as the Type 42AA or a Calibrator such as the Type 42AB.

## **RA0010**

### ***Adapter for Pistonphone calibration***

The RA0010 is an adapter for calibrating the Environmental Microphone Type 41AL. It fits over the rain protection cap of the Type 41AL and permits *in-situ* calibration using a Pistonphone such as the Type 42AA or a Calibrator such as the Type 42AB.

## **RA0041**

### ***Adapter for Pistonphone calibration***

The RA0041 is an adapter for calibrating the Outdoor Microphone System Type 41CN. It fits over the rain protection cap of the Type 41CN and permits *in-situ* calibration using a Pistonphone such as the Type 42AA or a Calibrator such as the Type 42AB.

### ***Extension cables for outdoor microphones***

The extension cables for the Outdoor Microphone Systems Types 41AM and 41CN (and the earlier Type 41CM) are high-quality PUR cables with a doubled-screened signal wire, terminated by 6-pin LEMO 2S connectors (for extension cables for the Environmental Microphone Type 41AL, see under Preamplifier Accessories and Cables).

| Cable length         | Type No. |
|----------------------|----------|
| 3 m                  | AA0003   |
| 10 m                 | AA0002   |
| 20 m                 | AA0001   |
| 30 m                 | AA0017   |
| 50 m                 | AA0004   |
| 100 m, on cable drum | AA0015   |
| 200 m, on cable drum | AA0016   |

**G.R.A.S.**  
**Sound & Vibration**

Skovlytoften 33  
2840 Holte, Denmark  
Tel +45 45 66 40 46 Fax +45 45 66 40 47  
e-mail: gras@gras.dk www.gras.dk

